



WALACE® PVC CORNER PROFILE WITH MESH

DESCRIPTION

PVC Corner Profile with mesh are a part of the WalAce System and are applied on the outer corner of the Wall. The profiles come with a PVC profile with reinforcement mesh gives an ease of application and maintain alignment of the edges.

TECHNICAL CHARACTERISTICS

PVC profile with fiberglass mesh with anti-alkaline treatment.

ADVANTAGES AND USES

- Easy to apply.
- Impact resistant as corners are reinforced
- Ease of alignment of corners

APPLICATION PROCEDURE

Apply the thin coat of WalAce Mortar to the edges of the WalAce Insulation panels. Press gently the profile over the edge. Check the alignment and adjust the level of the profile correctly. Cover the mesh with WalAce Mortar and allow it to dry for at least 24 hours.

RECOMMENDATIONS

- At the junction of two profiles, leave a distance of 1 to 2 mm.
- Joints between the profiles should not coincide with the joints of the insulation panels
- Once the profile is installed, leave to dry for at least 24 hours

PACKAGING AND STORAGE

Box: 2.5m each X 50 pieces

TECHNICAL DATA

(Data obtained in a laboratory under standard conditions)

Composition	PVC and Fiberglass with anti-alkaline treatment
Mesh weight	0.11 Kg/m
Profile length	2.5 m

WALACE EXTERNAL THERMAL WALACE® PVC CORNER PROFILE WITH MESH

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by PIDILITE GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

PIDILITE GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of PIDILITE GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by PIDILITE GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.