

UNOFIN CLASSIC BASECOAT

Dry plastering mortar.



DESCRIPTION

Dry mortar for plastering and masonry jobs in general.

TECHNICAL CHARACTERISTICS

Product based on high resistance cement, selected aggregates, and other additives

ADVANTAGES AND USES

- To be applied directly on brickworks.
- Masonry works.
- Plaster and stucco works

SUITABLE SUBSTRATES

- Conventional cement and brickwork based substrates.
- Substrates must be resistant, stable, sound and clean, free of dust, demolding agents, organic products, etc.
- In case of hot or windy weather conditions or when applying over absorbent substrates, it is advisable to wet the substrate and wait till the thin layer of water disappears.
- Do not apply on gypsum or on paint.

APPLICATION PROCEDURE

- Add water and mix by hand or mechanically until it takes on an even and workable consistency.
- For plaster works, spread the mortar on the substrate with a trowel and let rest enough time before floating.

RECOMMENDATIONS

- Do not apply under freezing conditions or rain.
- During periods of extreme heat, we make the following recommendations:
 - Wet the substrate before application
 - Store water and mortar bags out of direct sunlight
 - Provide shade where possible
- For a thickness of over 1.5 cm, it is advisable to apply the product in two coats.
- In extreme weather conditions (strong winds or high temperatures) it is necessary to water the product with light sprinklers the day after applying it.
- An excess of water may increase shrinkage and reduce mechanical resistance.
- The cladding must be interrupted at the level of the structural joints.
- It is not advisable to apply on horizontal or sloped surfaces.
- Carry out a good joint design, foreseeing expansion joints, structural ones, as well as those others that could be necessary.
- Protect the starting point of the plaster from capillary humidity placing a plinth at the base of the wall
- Special areas where the coating suffers tensions derived from the structure or due to the meeting of materials of a different nature on the substrate.
- A suitable treatment for these areas consists of incorporating a reinforcing mesh embedded in the mortar, to reinforce it and prevent it from cracking.



UNOFIN CLASSIC

UNOFIN CLASSIC BASECOAT

PACKAGING AND STORAGE

TECHNICAL DATA

CURING

- Between 5 and 30 °C, curing not required.
- Between 30 and 35 °C, wetting the following day, 2 times per day.
- Between 35 and 45 °C, wetting the following 72 hours, 2 times per day.

25 kg plastic-lined paper bags.

Shelf life: 1 year in sealed original packaging, sheltered from weather conditions and humidity.

Statistical data obtained under standard conditions

Aspect	GREY powder
Adhesion	$\geq 0,2 \text{ N/mm}^2$
UNE-EN 998-1 Classification	GP CSIV W0
Compressive Strength after 28 days	8 - 10 MPA
Approximate yield	
AAC Blocks	18-19 Kg/m ² /cm
Red Bricks	19-21 Kg/m ² /cm
Concrete Surfaces	18-19 Kg/m ² /cm
Powder Density	1.60±0.2 g/cm ³
Density of mass	1.90±0.2 g/cm ³
Mixed Water	15±1%
* The above yield may vary depending upon the several crucial factors, viz. substrate level, substrate condition, undulation, application thickness, etc. To ensure accurate and effective consumption, we strongly recommend conducting a mockup on site before final application.	

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by PIDILITE GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

PIDILITE GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of PIDILITE GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by PIDILITE GRUPO PUMA's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.