

DECLARATION OF PERFORMANCES

Nº: 100020


1. **Product:**
PEGOLAND SUPERFLEX BLANCO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Improved highly deformable cementitious adhesive with reduced slip and extended open time, PEGOLAND SUPERFLEX BLANCO, for bonding floor and wall tiles in interior and exterior applications. Especially suitable for façades, large surface floors, radiant heating floors, overlays, cold rooms, pools, and cementitious waterproofing.
4. **Evaluation system:**
3
5. **Notified bodies:**
Type tests were conducted under report numbers 001-22/028186/1, 001-22/028185/1, 001-22/028188/1 and 001-22/028189/1, dated September 2022, and 001-23/003057/1, dated January 2023, and 001-23/015402/1, dated May 2023, at CEMOSA nº 1377 (Málaga).
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze–thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performance of the product identified in point 1 conforms with the declared performance in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on manufacturer behalf:

Place and Date of issue: Málaga, 08/01/2025



Technical Director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 22	
PEGOLAND SUPERFLEX BLANCO N°: 100020 EN-12004:2007+A1:2012 Improved highly deformable cementitious adhesive with reduced slip and extended open time, for bonding floor and wall tiles in interior and exterior applications. Especially suitable for façades, large surface floors, radiant heating floors, overlays, cold rooms, pools, and cementitious waterproofing.	
Reaction to fire:	Type E
Adhesion: - Initial tensile adhesion strength:	≥ 1N/mm ²
Durability: - Tensile adhesion strength after water immersion:	≥ 1N/mm ²
- Tensile adhesion strength after heat ageing:	≥ 1N/mm ²
- Tensile adhesion strength after freeze–thaw cycles:	≥ 1N/mm ²
Hazardous substances:	See safety datasheet