

DECLARATION OF PERFORMANCES


Nº: 120100

1. **Product:**
PEGOLAND PORCELÁNICO BLANCO
2. **Manufacturer:**
3. **GRUPO PUMA ESPAÑA SL** located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
4. **Intended use :**
Normal-setting cementitious adhesive with reduced slip and extended open time, PEGOLAND PORCELÁNICO BLANCO, for bonding all types of ceramic tiles on interior and exterior floors and interior wall coverings. Suitable for swimming pool linings with glass mosaic.
5. **Evaluation system:**
3
6. **Notified bodies:**
Tests were conducted under type nº 71346 ,71384,71405,71434 ,71487, 74049, 75253, 75394, 75451, 75465, 75471,75475, in February, March, April 2004 and nº 2508369 in August 2005, at CEMOSA nº 1377 (Málaga) and nº 23010056, 4019119 in February and September 2004, nº 08-5019 in October 2008, at APPLUS nº 0370 (Barcelona) . The results obtained were consistent for the product across all factories.
7. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6. The present declaration of performance is issued in accordance with Regulation (EU) nº2024/3110, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer's behalf:
Place and date of issue: Málaga, 07/01/2025



Technical director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND PORCELÁNICO BLANCO Nº: 120100 EN-12004:2007+A1:2012 Normal-setting cementitious adhesive with reduced slip and extended open time, PEGOLAND PORCELÁNICO BLANCO, for bonding all types of ceramic tiles on interior and exterior floors and interior wall coverings. Suitable for swimming pool linings with glass mosaic.	
Reaction to fire:	Type E
Adhesion:	
- Initial tensile adhesion strength:	$\geq 0.5\text{N/mm}^2$
Durability:	
- Tensile adhesion after water immersion:	$\geq 0.5\text{N/mm}^2$
- Tensile adhesion after heat aging:	$\geq 0.5\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles:	$\geq 0.5\text{N/mm}^2$
Hazardous substances:	See safety datasheet