

DECLARATION OF PERFORMANCES

Nº: 120018

1. **Product:**
PEGOLAND PLUS GRIS
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Normal-setting cementitious adhesive with reduced slip, PEGOLAND PLUS GRIS, for bonding tiles with medium to high water absorption on interior and exterior floors, and interior walls.
4. **Evaluation system:**
3
5. **Notified bodies:**
Type tests No. 71383, 71410, 71436, 71448, 73591, 75254, 75454, 75469 and 80106 were carried out in February, March, April, May and June 2004, Test No. 2703403 in March 2007, Test No. 0201-01-2013-7062 in October 2013, and Test No. 01-21/010855/1 in April 2021 at CEMOSA No. 1377 (Málaga). In addition, Test No. 4019120 in November 2004, Test No. 5029471 in July 2005, and Test No. 31212761 in August 2006 were carried out at APPLUS No. 0370 (Barcelona), obtaining the same product performance results for all manufacturing plants.
6. **Declared performances:**


Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.

This Declaration of Performance is issued, in accordance with **Regulation (EU) 2024/3110**, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on manufacturer behalf:

Place and Date of issue: Málaga, 07/01/2025



Technical Director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND PLUS GRIS Nº: 120018 EN-12004:2007+A1:2012 Normal-setting cementitious adhesive with reduced slip, for bonding tiles with medium to high water absorption on interior and exterior floors, and interior walls.	
Reaction to fire:	Type E
Adhesion: - Initial tensile adhesion strength:	≥ 0.5N/mm ²
Durability: - Tensile adhesion strength after water immersion: - Tensile adhesion strength after heat ageing: - Tensile adhesion strength after freeze-thaw cycles:	≥ 0.5N/mm ² ≥ 0.5N/mm ² ≥ 0.5N/mm ²
Hazardous substances:	See safety datasheet