

DECLARATION OF PERFORMANCES

Nº: 603856

1. **Product:**
MORCEMDUR RASPADO FINO
2. **Manufacturer:**
GRUPO PUMA SL located in:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:** Monolayer plaster mortar OC CSIII W2, for façade finishing and rain protection with finish fine scraping.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN 998-1:2018
Water absorption	W2	
Water permeability after climatic cycles conditioned	≤ 1 ml/cm ² after 48 hours	
Diffusion coefficient of water vapour	μ≤15	
Thermal conductivity (λ10,seco)	PND	
Adhesion after climatic cycles conditioned	≥ 0,3 N/mm ² Form A/B breakage	
Durability	Evaluation based on provisions valid in the intended place of use of the mortar	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 5. This declaration of features is issued under the sole responsibility of manufacturer stated in point 2, in accordance with Regulation (EU) N° 305/2011.

Signed by and on manufacturer behalf.
Place and date of issue: Cordoba, 14/11/2022



Technical director: José A. Ferre Martínez



GRUPO PUMA S.L
 Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
 14014 CÓRDOBA
 18

MORCEMDUR RASPADO FINO
Nº: 603856
EN 998-1

Monolayer plaster mortar OC CSIII W2, for façade finishing and rain protection with finish fine scraping.

Reaction to fire	Type A1
Water absorption	W2
Water permeability after climatic cycles conditioned	≤ 1 ml/cm ² after 48 hours
Diffusion coefficient of water vapour	μ≤15
Adhesion after climatic cycles conditioned	≥ 0,3 N/mm ² Form A/B breakage