

DECLARATION OF PERFORMANCES

Nº: 100195-186


1. **Product:**
PEGOLAND FLEX RECORD
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Av. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Improved cementitious adhesive, highly deformable, with reduced slip and extended open time, Pegoland Flex Record, for the installation of large-format tiles of all absorption levels on large surfaces; for interior and exterior floor tiling, interior and exterior wall tiling, façades, underfloor heating systems, cold rooms, overlays on marble, granite, terrazzo, natural stone and all types of ceramic substrates on interior and exterior floors and interior wall coverings; for swimming pool linings and installation over cementitious waterproofing systems; suitable for bonding all types of ceramic tiles, porcelain stoneware, marble, granite and natural stone.
4. **Evaluation system:**
3
5. **Notified bodies:**
Tests were conducted under type nº 76709 dated April 1, 2004 at CEMOSA nº 1377 (Málaga).
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6
The present declaration of performance is issued in accordance with Regulation (EU) nº2024/3110, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 08/01/2025



Technical director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND FLEX RECORD Nº: 100195-186 EN 12004:2007+A1:2012 Improved cementitious adhesive, highly deformable, with reduced slip and extended open time, Pegoland Flex Record, for the installation of large-format tiles of all absorption levels on large surfaces; for interior and exterior floor tiling, interior and exterior wall tiling, façades, underfloor heating systems, cold rooms, overlays on marble, granite, terrazzo, natural stone and all types of ceramic substrates on interior and exterior floors and interior wall coverings; for swimming pool linings and installation over cementitious waterproofing systems; suitable for bonding all types of ceramic tiles, porcelain stoneware, marble, granite and natural stone.	
Reaction to fire:	Type E
Adhesion: - Initial tensile adhesion strength:	≥ 1N/mm ²
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	≥1N/mm ² ≥1N/mm ² ≥1N/mm ²
Hazardous substances:	See safety datasheet