



DECLARATION OF PERFORMANCES

Nº: 340001

1. **Product:**
PEGOLAND ELASTIC (R2T)
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL based in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba).
www.grupopuma.com
3. **Intended use:**
Improved reaction resin adhesive for ceramic tiles (R2), for the installation of ceramic tiles on interior and exterior floors and walls.
4. **Evaluation system:**
3
5. **Notified Agencies:**

The notified body Modena Centro Prove S.r.l., Modena – Italy – No. 1599, has determined the shear adhesion strength on a sample taken at the manufacturer's premises, according to System 3, and has issued Test Report No. 20188770/1.

6. Declared performances:

Essential characteristics	Performances	Harmonized standards
Reaction to fire :	Class E	EN-12004:2007 + A1:2012
Initial shear strength	$\geq 2 \text{ N/mm}^2$	
Shear resistance after immersion in water	$\geq 2 \text{ N/mm}^2$	
Shear resistance after thermal shocks	$\geq 2 \text{ N/mm}^2$	
Hazardous substances	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6. This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 07/03/2025

Technical director: Jose A. Ferre Martínez

 1599	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 19	
PEGOLAND ELASTIC Nº: 340001 EN 12004: 2007 + A1:2012 Improved reaction resin adhesive for ceramic tiles (R2), for the installation of ceramic tiles on interior and exterior floors and walls.	
Reaction to fire:	Class E
Performances: - Initial shear strength: $\geq 2\text{N/mm}^2$ - Shear resistance after immersion in water: $\geq 2\text{N/mm}^2$ - Shear resistance after thermal shocks: $\geq 2\text{N/mm}^2$	
Hazardous substances:	See safety datasheet