

DECLARATION OF PERFORMANCES

Nº: 07/0054

- 1. Product:**
TRADITERM SYSTEM
- 2. Manufacturer:**
GRUPO PUMA SL located in:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
- 3. Intended use:**
Exterior Thermal Insulation System with plaster for building walls
- 4. Evaluation system:**
2+
- 5. Notified bodies:**
Eduardo Torroja Institute of Construction Sciences (IETcc) (ON) –nº 1219–
- 6. European technical assessment and factory production control:**
ETE 07/0054 according to EAD 040083-00-0404
- 7. Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type B-s1 d0	UNE-EN 13501-1
Water absorption	< 0.5 kg/m ²	EAD 040083-00-0404
Impact resistance	Category I to III depending on system configuration	
Permeability to water vapour	<1 m	
Adherence: Base coat on thermal insulation (EPS/EPS-G, XPS)"	> 0,08 N/mm ²	
Adherence: Base coat on thermal insulation (MW)	> 0,03 N/mm ²	
Adherence: Adhesive on thermal insulation (EPS/EPS-G, XPS)"	> 0,08 N/mm ²	
Adherence: Adhesive on thermal insulation (MW)	> 0,03 N/mm ²	
Adherence: Adhesive on concrete	> 0,25 N/mm ²	
Hygrothermal behavior	Pass	
Freeze-thaw cycle behaviour	Pass	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 7.
This declaration of features is issued under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:
Place and date of issue: Córdoba, 31/01/23



Technical director: Jose A. Ferre Martínez



GRUPO PUMA SL
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
23

TRADITERM SYSTEM

Nº: 07/0054

EAD 040083-00-0404

Exterior Thermal Insulation System with plaster for building walls

Reaction to fire	Type B-s1 d0
Water absorption	< 0,5 kg/m ²
Impact resistance	Category I to III depending on system configuration
Permeability to water vapour	<1 m
Adherence: Base coat on thermal insulation (EPS/EPS-G, XPS)"	> 0,08 N/mm ²
Adherence: Base coat on thermal insulation (MW)	> 0,03 N/mm ²
Adherence: Adhesive on thermal insulation (EPS/EPS-G, XPS)"	> 0,08 N/mm ²
Adherence: Adhesive on thermal insulation (MW)	> 0,03 N/mm ²
Adherence: Adhesive on concrete	> 0,25 N/mm ²
Freeze-thaw cycle behaviour	Pass
Behavior of freeze-thaw cycles	Pass