

DECLARATION OF PERFORMANCES


Nº: 120117

1. **Product:**
PEGOLAND PORCELÁNICO GRIS
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Normal-setting cementitious adhesive with reduced slip and extended open time, PEGOLAND PORCELÁNICO GREY, for bonding all types of ceramic tiles on interior and exterior floors and interior wall coverings. Suitable for swimming pool linings with glass mosaic.
4. **Evaluation system:**
3
5. **Notified bodies:**
Tests were conducted under type nº 71347, 71386, 71406, 71417, 71431, 71437, 71486, 75397, 75449, 75465 ,80107, in February, March, April, June 2004, at CEMOSA nº 1377 (Málaga) and nº 4021730 in September 2004 , nº 5029470, 5026638 in July and September 2005, nº 31212763 in August 2006 at APPLUS nº 0370 (Barcelona) . The results obtained were consistent for the product across all factories.
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
The present declaration of performance is issued in accordance with Regulation (EU) nº2024/3110, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer's behalf:
Place and date of issue: Málaga, 07/01/2025



Technical director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND PORCELÁNICO GRIS Nº: 120117 EN-12004:2007+A1:2012 Normal-setting cementitious adhesive, with reduced slip and extended open time, for floors and walls, suitable for interior and exterior applications	
Reaction to fire:	Type E
Adhesion: - Initial tensile adhesion strength: $\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion: $\geq 0.5\text{N/mm}^2$ - Tensile adhesion after heat aging: $\geq 0.5\text{N/mm}^2$ - Tensile adhesion after freeze/thaw cycles: $\geq 0.5\text{N/mm}^2$	
Hazardous substances:	See safety datasheet