

## DECLARATION OF PERFORMANCES

### Nº: 501869-01

1. **Product:**  
PAVILAND SOLERA R AUTONIVELANTE
2. **Manufacturer:**  
GRUPO PUMA ESPAÑA S.L located in: Avda.  
AGRUPACIÓN CÓRDOBA, Núm. 17 14014  
CÓRDOBA  
[www.grupopuma.com](http://www.grupopuma.com)
3. **Intended use:**  
CT C25 F5 B1 5 type, fast-setting, self-levelling, screed mortar for interior floors, 50 mm when adhered and 100 mm when non-adhered.
4. **Evaluation system:**  
4
5. **Declared performances:**

| Essential characteristics        | Performance                | Harmonized technical specification |
|----------------------------------|----------------------------|------------------------------------|
| Reaction to fire                 | A1 Class                   | EN 13813:2014                      |
| Emission of corrosive substances | CT                         |                                    |
| Water permeability               | NPD                        |                                    |
| Water vapor permeability         | NPD                        |                                    |
| Compressive strength             | C25                        |                                    |
| Flexural strength                | F5                         |                                    |
| Resistance to traction           | B1,5                       |                                    |
| Wear strength                    | NPD                        |                                    |
| Sound insulation                 | NPD                        |                                    |
| Acoustic absorption              | NPD                        |                                    |
| Thermal resistance               | NPD                        |                                    |
| Chemical resistance              | NPD                        |                                    |
| Hazardous substances             | Consult safety data sheet. |                                    |

The performances of the product identified in point 1 are conform with the declared performances in point 5.  
This Declaration of Performances is issued under the sole responsibility of the manufacturer indicated in point 2 in accordance with Regulation (EU) No 305/2011.

Signed by and on manufacturer's behalf:  
Place and date of issue: Córdoba, 10/02/26



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA ESPAÑA, S.L  
 Avda. AGRUPACIÓN CÓRDOBA, Núm. 17  
 14014 CÓRDOBA

26

**PAVILAND SOLERA R AUTONIVELANTE**

**Nº: 501869-01**

**EN 13813**

CT C25 F5 B1 5 type, fast-setting, self-levelling, screed mortar for interior floors, until 50 mm thickness when adhered and until 100 mm when non-adhered.

|   |                            |
|---|----------------------------|
| <b>Reaction to fire</b>                 | A1 Class                   |
| <b>Emission of corrosive substances</b> | CT                         |
| <b>Compressive strength</b>             | C25                        |
| <b>Flexural strength</b>                | F5                         |
| <b>Resistance to traction</b>           | B1,5                       |
| <b>Hazardous substances</b>             | Consult safety data sheet. |