



## DECLARATION OF PERFORMANCES Nº: 501870-01

- 1. Product:**  
NIVELAND 10
- 2. Manufacturer:**  
GRUPO PUMA S.L located in:  
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17  
14014 CÓRDOBA  
www.grupopuma.com
- 3. Intended use:**  
Self-leveling cementitious paste, type CT C25 F5, for the preparation of interior floors and the installation of lightweight floorings such as ceramic tiles, parquet, carpet, etc., suitable for thicknesses ranging from 2 to 10 mm.
- 4. Evaluation system:**  
4
- 5. Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN 13813:2014
Emission of corrosive substances	CT	
Water permeability	NPD	
Water vapor permeability	NPD	
Compression Strength	C25	
Flexural strength	F5	
Acoustic insulation	NPD	
Acoustic absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Hazardous substances	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2 in accordance with Regulation (EU) No 305/2011.

Signed by and on behalf of the manufacturer:  
Place and Date of issue: Córdoba, 24/08/2021

Technical director: Jose A. Ferre



<b>CE</b>	
GRUPO PUMA S.L Avda. AGRUPACIÓN CÓRDOBA, Núm. 17 14014 CÓRDOBA	
18	
<b>NIVELAND 10</b>  <b>Nº: 501870-01</b>  <b>EN 13813</b>	
Self-leveling cementitious paste, type CT C25 F5, for the preparation of interior floors and the installation of lightweight floorings such as ceramic tiles, parquet, carpet, etc., suitable for thicknesses ranging from 2 to 10 mm.	
<b>Reaction to fire</b>	Type A1
<b>Emission of corrosive substances</b>	CT
<b>Compression Strength</b>	C25
<b>Flexural strength</b>	F5
<b>Hazardous substances</b>	See safety datasheet