

## DECLARATION OF PERFORMANCES

Nº: 130024


1. **Product:**  
TRADICOL EXTERIORES BLANCO
2. **Manufacturer:**  
GRUPO PUMA ESPAÑA SL located in:  
Avda. Agrupación Córdoba, 17  
14014 Córdoba (Córdoba)  
www.grupopuma.com
3. **Intended use:**  
Normal-setting cementitious adhesive with reduced slip, TRADICOL EXTERIORES BLANCO, for thick-bed installation on brick walls and for floor tiling over uneven substrates using tiles with high, medium or low water absorption.
4. **Evaluation system:**  
3
5. **Notified bodies:**  
Type tests No. 78238, 78241, 78244, 79192, 79620, 84065 and 85393 were carried out in June, August and September 2004, and Tests No. 84847, 96508 and 2501885 in March and June 2005, at CEMOSA No. 1377 (Málaga). In addition, Tests No. 5026662 and 5027615 were carried out in September 2005, and Tests No. 07/31200749 and 07/31200753 in February 2007, at APPLUS No. 0370 (Barcelona), obtaining the same product performance results for all manufacturing plants.
6. **Declared performances:**

| Essential characteristics                                                                                                                                                        | Performance                                                                   | Harmonised technical specification |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|------------------------------------|
| <b>Reaction to fire:</b>                                                                                                                                                         | Type E                                                                        | EN-12004:2007+A1:2012              |
| <b>Adhesion:</b><br>- Initial tensile adhesion strength                                                                                                                          | $\geq 0.5\text{N/mm}^2$                                                       |                                    |
| <b>Durability:</b><br>- Tensile adhesion strength after water immersion<br>- Tensile adhesion strength after heat ageing<br>- Tensile adhesion strength after freeze-thaw cycles | $\geq 0.5\text{N/mm}^2$<br>$\geq 0.5\text{N/mm}^2$<br>$\geq 0.5\text{N/mm}^2$ |                                    |
| <b>Hazardous substances:</b>                                                                                                                                                     | See safety datasheet                                                          |                                    |

The performances of the product identified in point 1 comply with the performance declared in point 6  
The present declaration of performance is issued in accordance with Regulation (EU) nº305/2011, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:

Place and Date of issue: Málaga, 07/01/2025



Technical Director: Jose A. Ferre Martínez

|                                                                                                                                                                                                                                        |                                                                               |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| <br>0370, 1377                                                                                                                                        |                                                                               |
| GRUPO PUMA ESPAÑA SL<br>Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba)<br>04                                                                                                                                                      |                                                                               |
| <b>TRADICOL EXTERIORES BLANCO</b><br><br><b>Nº: 130024</b><br><br><b>EN-12004:2007+A1:2012</b><br><br>Normal-setting cementitious adhesive with reduced slip for floors and walls,<br>suitable for interior and exterior applications. |                                                                               |
| <b>Reaction to fire:</b>                                                                                                                                                                                                               | Type E                                                                        |
| <b>Adhesion:</b><br>- Initial tensile adhesion strength:                                                                                                                                                                               | $\geq 0.5\text{N/mm}^2$                                                       |
| <b>Durability:</b><br>- Tensile adhesion strength after water immersion:<br>- Tensile adhesion strength after heat ageing:<br>- Tensile adhesion strength after freeze-thaw cycles:                                                    | $\geq 0.5\text{N/mm}^2$<br>$\geq 0.5\text{N/mm}^2$<br>$\geq 0.5\text{N/mm}^2$ |
| <b>Hazardous substances:</b>                                                                                                                                                                                                           | See safety datasheet                                                          |