

DECLARATION OF PERFORMANCES

Nº: 120001

1. Product:

PEGOLAND PLUS BLANCO

2. Manufacturer:

GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com

3. Intended use:

Normal-setting cementitious adhesive with reduced slip, PEGOLAND PLUS BLANCO, for bonding tiles with medium to high water absorption on interior and exterior floors, and interior wall coverings.

4. Evaluation system:

3

5. Notified bodies:

Type tests No. 71349, 71385, 71409, 71432, 71435, 74048, 74640, 75181, 75255, 75453, 75458, 75472 and 76378 were carried out in February, March and April 2004, and Test No. 201/1/2011/1049 in May 2011 at CEMOSA No. 1377 (Málaga). In addition, Tests No. 4019118 and 4025971 were carried out in September 2004 at APPLUS No. 0370 (Barcelona), obtaining the same product performance results for all manufacturing plants.

6. Declared performances:


Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 0.5\text{N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$ $\geq 0.5\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.

This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on manufacturer behalf:

Place and Date of issue: Málaga, 07/01/2025



Technical Director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND PLUS BLANCO Nº: 120001 EN-12004:2007+A1:2012 Normal-setting cementitious adhesive with reduced slip, for bonding tiles with medium to high water absorption on interior and exterior floors, and interior wall coverings.	
Reaction to fire:	Type E
Adhesion: - Initial tensile adhesion strength:	≥ 0.5N/mm ²
Durability: - Tensile adhesion strength after water immersion: - Tensile adhesion strength after heat ageing: - Tensile adhesion strength after freeze-thaw cycles:	≥ 0.5N/mm ² ≥ 0.5N/mm ² ≥ 0.5N/mm ²
Hazardous substances:	See safety datasheet