

DECLARATION OF PERFORMANCES


Nº: 105283

1. **Product:**
PEGOLAND FAST FLEX
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Improved fast-setting, deformable cementitious adhesive with extended open time and reduced slip, PEGOLAND FAST FLEX, for the installation of interior and exterior floor and wall tiles; suitable for façades, underfloor heating systems, cold rooms, large surface floors, overlays, swimming pools and installation over cementitious waterproofing systems; suitable for bonding all types of ceramic tiles, porcelain stoneware, marble, granite and natural stone.
4. **Evaluation system:**
3
5. **Notified bodies:**
Tests were conducted under type nº 0201-01-2014-4479 dated June 23, 2014 at CEMOSA nº 1377 (Málaga).
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Early tensile strength adhesion. - Initial tensile adhesion strength	$\geq 0.5\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
The present declaration of performance is issued in accordance with Regulation (EU) nº2024/3110, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:
Place and date of issue: Málaga, 08/1/25



Technical director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 14	
PEGOLAND FAST FLEX Nº: 105283 EN-12004:2007+A1:2012 Improved fast-setting cementitious adhesive with extended open time, reduced slip and high deformability, for the installation of all types of ceramic tiles on interior and exterior floors and walls, especially suitable for façades.	
Reaction to fire:	Type E
Adhesion: - Early tensile strength adhesion: $\geq 0.5\text{N/mm}^2$ - Initial tensile adhesion strength: $\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion: $\geq 1\text{N/mm}^2$ - Tensile adhesion after heat aging: $\geq 1\text{N/mm}^2$ - Tensile adhesion after freeze/thaw cycles: $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet