

DECLARATION OF PERFORMANCES

Nº: 105305

1. **Product:**
PEGOLAND GEL S2 GRIS
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Improved highly deformable cementitious adhesive with reduced slip and extended open time, PEGOLAND GEL S2 GRIS, for bonding floor and wall tiles, indoors and outdoors; especially suitable for façades, large surface floors, large-format and/or thin tiles, underfloor heating systems, overlays, cold rooms, swimming pools and installation over cementitious waterproofing systems.
4. **Evaluation system:**
3
5. **Notified bodies:**
Tests were conducted under type nº 001-22/005964/1, nº 001-22/005966/1, nº 001-22/005945/1 in February 2022, nº 001-22/009080/1 in March 2022 and nº 001-22/036948/1 in November 2022 at CEMOSA nº 1377 (Málaga). The results obtained were consistent for the product across all factories.
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
The present declaration of performance is issued in accordance with Regulation (EU) nº2024/3110, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:
Place and date of issue: Málaga, 08/01/2025



Technical director: Jose A. Ferre Martínez



1377

GRUPO PUMA ESPAÑA SL
Avda. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba)
22

PEGOLAND GEL S2 GRIS
Nº: 105305
EN 12004:2007+A1:2012

Improved highly deformable cementitious adhesive with reduced slip and extended open time, for floors, walls and façades, suitable for interior and exterior applications.

Reaction to fire:	Type E
--------------------------	--------

Adhesion:	
- Initial tensile adhesion strength:	$\geq 1\text{N/mm}^2$

Durability:	
- Tensile adhesion after water immersion:	$\geq 1\text{N/mm}^2$
- Tensile adhesion after heat aging:	$\geq 1\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles:	$\geq 1\text{N/mm}^2$

Hazardous substances:	See safety datasheet
------------------------------	----------------------