

DECLARATION OF PERFORMANCES

Nº : 100010-143

1. **Product:**
PEGOLAND PORCELANICO FLEXIBLE BLANCO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Improved deformable cementitious adhesive with reduced slip and extended open time, Pegoland Porcelánico Flexible Blanco, for the installation of interior and exterior floors, interior walls and plinths, swimming pool rendering, underfloor heating, overlays in interior flooring, adhesion of all types of ceramic pieces, porcelain tiles, marble, granite, and natural stone.
4. **Evaluation system:**
3
5. **Notified bodies:**
Type tests were carried out under report number 01-18/000689/1, dated November 2017; report numbers 01-21/001077/1, 01-21/000832/1 and 01-21/003987/1, dated January 2021; report numbers 01-21/002814/1 and 01-21/003982/1, dated February 2021; report numbers 01-21/005945/1, 01-21/006033/1, 01-21/005777/1, 01-21/007635/1, 01-21/006975/1 and 01-21/007520/1, dated March 2021; and report number 01-21/020247/1, dated June 2021, at CEMOSA (No. 1377, Málaga), obtaining identical product performance results for all manufacturing plants.
6. **Declared performances:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	E Type	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 6.

This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2. Signed by and on manufacturer's behalf:
Place and ate of issue: Málaga, 03/01/2025



Technical Director: Jose A. Ferre Martínez

 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 17	
PEGOLAND PORCELANICO FLEXIBLE BLANCO N.º: 100010-143 EN-12004:2007+A1:2012 Improved cementitious adhesive with reduced slip and extended open time, suitable for interior and exterior walls and floors.	
Reaction to fire:	Type E
Adhesion: - Initial tensile adhesion strength:	≥ 1N/mm ²
Durability: - Tensile adhesion strength after water immersion: - Tensile adhesion strength after heat ageing: - Tensile adhesion strength after freeze–thaw cycles:	≥ 1 N/mm ² ≥ 1 N/mm ² ≥ 1 N/mm ²
Hazardous substances:	See safety data sheet