

DECLARATION OF PERFORMANCES

Nº: 105285-399

1. **Product:**
PEGOLAND GEL S2 BLANCO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Av. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
Improved highly deformable cementitious adhesive with reduced slip and extended open time, PEGOLAND GEL S2 BLANCO, for bonding floor and wall tiles, indoors and outdoors; especially suitable for façades, large surface floors, large-format and/or thin tiles, underfloor heating systems, overlays, cold rooms, swimming pools and installation over cementitious waterproofing systems.
4. **Evaluation system:**
3
5. **Notified bodies:**
Tests were conducted under type nº 01-15/000911/1, in February 2015, nº 01-20/009083/1 in March 2020, and nº 01-20/011302/1 in April 2020, at CEMOSA nº 1377 (Málaga) and nº 18/14017-63, nº 18/16382-184, nº 18/16354-752 in March 2018, nº 18/16883-930, nº 18/16881-918, nº 18/16882-924 in April 2018 at APPLUS nº 0370 (Barcelona) . The results obtained were consistent for the product across all factories.
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
The present declaration of performance is issued in accordance with Regulation (EU) nº2024/3110, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:
Place and date of issue: Málaga, 08/01/2025



Technical director: Jose A. Ferre Martínez



0370, 1377

GRUPO PUMA ESPAÑA SL
Av. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
15

**PEGOLAND GEL S2
BLANCO**

**Nº: 105285-399
EN 12004:2007+A1:2012**

Improved highly deformable cementitious adhesive with reduced slip
and extended open time, for floors, walls and façades, suitable for
interior and exterior applications.

Reaction to fire: Type E

Adhesion:

- Initial tensile adhesion strength: $\geq 1\text{N/mm}^2$

Durability:

- Tensile adhesion after water immersion: $\geq 1\text{N/mm}^2$
- Tensile adhesion after heat aging: $\geq 1\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles: $\geq 1\text{N/mm}^2$

Hazardous substances: See safety datasheet