

DECLARATION OF PERFORMANCES

Nº: 200024-1

1. **Product:**
MORCEM GLASS
2. **Manufacturer:**
GRUPO PUMA S.L with registered address at:
Avda. AGRUPACIÓN CÓRDOBA, Núm. 17
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Argamassa de alvenaria prescrita para alvenaria de uso geral (G), para trabalhos em blocos de vidro e betumação.
4. **Evaluation system:**
4
5. **Declared performances:**

Essential characteristics	Performances	Harmonised technical specification
Proportion of components (by volume)	Cement 33.5% Aggregates 66.4%	EN 998-2:2018
Bond strength	NPD	
Chloride ion content	NPD	
Reaction to fire	Class A1	
Water absorption	$\leq 0.4 \text{ Kg/m}^2 \cdot \text{min}^{0.5}$	
Water vapor diffusion coefficient	$\mu 15/35$	
Thermal conductivity:($\lambda 10, \text{dry}$)	NPD	
Durability	NPD	
Hazardous substances	See Safety Data Sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5. This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2, in accordance with regulation (EU) no. 305/2011.

Signed by and on behalf of the manufacturer:
Place and Date of issue: Cordoba, 26/08/21



Technical director: Jose A. Ferre Martínez

CE	
GRUPO PUMA S.L Avda. AGRUPACIÓN CÓRDOBA, Núm. 17 14014 CÓRDOBA 18	
MORCEM GLASS Nº: 200024-1 EN 998-2 Prescribed mortar for masonry of common use (G), to lift glass block works and grouting.	
Proportion of components (by volume): Cement 33.5% Aggregates 66.4%	
Reaction to fire	Class A1
Water absorption	$\leq 0.4 \text{ Kg/m}^2 \cdot \text{min}^{0.5}$
Water vapor diffusion coefficient	$\mu_{15/35}$