

DECLARATION OF PERFORMANCES

Nº: 100003

1. **Product:**
PEGOLAND FLEX BLANCO
2. **Manufacturer:**

GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com

3. **Intended use:**
4. Improved deformable cementitious adhesive with reduced slip and extended open time, Pegoland Flex Blanco, for the installation of interior and exterior floorings, interior and exterior walls, façades, underfloor heating, cold storage rooms, large area floors and overlays, pool rendering, and installation on cementitious waterproofing systems, adhesion of all type of ceramic pieces, porcelain stoneware, marble, granite, and other natural stone.
5. **Evaluation system:**
3
6. **Notified bodies:**
Type tests were carried out under report numbers 18/17090-1233, 18/17555-1991, 18/17129-1303, 18/17292-1503, 18/17043-1128, 18/17056-1157, 18/17587-2050, 18/17226-1411, 18/17536-1948, dated September 2018; report numbers 18/17962-2671 and 18/17962-2670, dated October 2018; report numbers 18/18552-3573, 18/18553-503, 19/18553-504 and 19/18554-146, dated January 2019; and report numbers 18/18546-3565, 18/18548-3566 and 18/18549-501, dated February 2019, at APPLUS+ Laboratories (No. 0370, Barcelona), obtaining identical product performance results for all manufacturing plants.
7. **Declared performances:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	E Class	EN 12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after thermal ageing - Tensile adhesion strength after freeze/thaw cycles	$\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$	
Hazardous substances:	See Safety Data Sheet	

The performance of the product identified in point 1 conforms with the declared performance in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on manufacturer's behalf:
Place and date of issue: Málaga, 08/01/2025



Technical Director: Jose A. Ferre Martínez

 0370	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 18	
PEGOLAND FLEX BLANCO Nº: 100003 EN 12004:2007+A1:2012 Improved deformable cementitious adhesive with reduced slip and extended open time, Pegoland Flex Blanco, for the installation of interior and exterior floorings, interior and exterior walls, façades, underfloor heating, cold storage rooms, large area floors and overlays, pool rendering, and installation on cementitious waterproofing systems.	
Reaction to fire:	E Class Type E
Adhesion:	
- Initial tensile adhesion strength:	$\geq 1 \text{ N/mm}^2$
Durability:	
- Tensile adhesion strength after water immersion:	$\geq 1 \text{ N/mm}^2$
- Tensile adhesion strength after thermal ageing:	$\geq 1 \text{ N/mm}^2$
- Tensile adhesion after freeze/thaw cycles:	$\geq 1 \text{ N/mm}^2$
Hazardous substances:	See Safety Data Sheet