


DECLARATION OF PERFORMANCES

Nº: 110132

1. **Product:**
PEGACOL BLANCO
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL
located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:** PEGACOL BLANCO cementitious adhesive for the installation of interior floor and wall tiles. Suitable for bonding ceramic tiles with medium to high water absorption. Not suitable for exterior applications.
4. **Evaluation system:**
3
5. **Notified bodies:** Type tests nº 71361, 71376, 71390, 71392, 71418, 71438, 71473, 71477, 71482, 73825, dated February, March, April and May 2004 and 2802735 April 2008 have been carried out in CEMOSA nº 1377 (Málaga), and tests nº 06/31211946, 09/1081-3153 dated April 2006 and January 2010 have been carried out in APPLUS nº 0370 (Barcelona), obtaining the same results of the product for all factories.
6. **Declared performances:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type A1 _n y A1	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	≥ 0.5 N/mm ²	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	≥ 0.5 N/mm ² NPD NPD	
Hazardous substances	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
This declaration of features is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of manufacturer stated in point 2.
Signed by and on manufacturer behalf.
Place and date of issue: Malaga, 02/01/2025



Technical director: José A. Ferre Martínez



0370, 1377

GRUPO PUMA ESPAÑA SL
Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba)
04

PEGACOL BLANCO
Nº: 110132
EN 12004: 2007+A1:2012

Cementitious adhesive for the installation of interior floor and wall tiles. Suitable for bonding ceramic tiles with medium to high water absorption. Not suitable for exterior applications.

Reaction to fire: Type A1_{fl} y A1

Adhesion:

- Initial tensile adhesion strength $\geq 0.5 \text{ N/mm}^2$

Durabilité:

- Tensile adhesion after water immersion $\geq 0.5 \text{ N/mm}^2$
- Tensile adhesion after heat aging NPD
- Tensile adhesion after freeze/thaw cycles NPD

Hazardous substances: See safety datasheet