

## DECLARACION OF PERFORMANCES Nº: 860037

1. **Product:**  
MORCEMCAL MURO
2. **Manufacturer:**  
GRUPO PUMA SL with registered address:  
Avda. AGRUPACIÓN CÓRDOBA, Núm.17  
14014 CÓRDOBA  
[www.grupopuma.com](http://www.grupopuma.com)
3. **Intended use:**  
Mortar for plastering and rendering for common use G, based on natural hydraulic lime, for the execution and repair of walls and factories.
4. **Evaluation system:**  
4
5. **Declared performances:**

| Essential characteristics                                    | Performances                               | Harmonized standards |
|--|--|----------------------|
| <b>Proportion of components</b>                              | Cement: 0%<br>Lime: 47%<br>Aggregates: 53% | EN-998-2:2012        |
| <b>Adhesion</b>  | NPD  |                      |
| <b>Chloride content</b>                                      | NPD  |                      |
| <b>Reaction to fire</b>                                      | Class A1                                   |                      |
| <b>Water absorption</b>                                      | NPD  |                      |
| <b>Water vapor permeability</b>                              | $\leq \mu 6$                               |                      |
| <b>Thermal conductivity (<math>\lambda_{10}</math>, dry)</b> | NPD  |                      |
| <b>Durability</b>  | NPD  |                      |
| <b>Hazardous substances</b>                                  | See safety data sheet                      |                      |

The performance of the product identified in point 1 is in conformity with the performance declared in point 5.  
This declaration of performance is issued under the sole responsibility of the manufacturer indicated in point 2.  
Signed by and on behalf of the manufacturer:  
Place and Date of issue: Córdoba, 24/07/2020



Technical director: Jose A. Ferre Martínez



GRUPO PUMA SL  
 Avda. Agrupación Córdoba, Núm.17  
 14014 CÓRDOBA  
 11

**MORCEMCAL MURO**

**Nº: 860037**

**EN 998-2**

Mortar for plastering and rendering for common use G,  
 based on natural hydraulic lime, for the execution and  
 repair of walls and factories.

|                                 |  |
|---------------------------------|--|
| <b>Proportion of components</b> | Cement: 0%<br>Lime: 47%<br>Aggregates: 53% |
| <b>Reaction to fire</b>         | Class A1                                   |
| <b>Water vapor permeability</b> | $\mu \leq 6$                               |