

DECLARATION OF PERFORMANCES

Nº: 100595

1. Product:

PEGOLAND GEL S1 GRIS

2. Manufacturer:

GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com

3. Intended use:

Improved deformable cementitious adhesive with reduced slip and extended open time, PEGOLAND GEL S1 GRIS, for bonding wall and floor tiles, suitable for interior and exterior applications; especially for façades, large surface floors, large-format tiles, overlays, cold rooms, underfloor heating systems, swimming pools and installation over cementitious waterproofing systems.

4. Evaluation system:

3

5. Notified bodies:

Tests were conducted under type nº 01-19/032365/1 in August 2019, 01-20/022675/1 in July 2020, 01-21/007371/1 in March 2021, 01-21/014841/1 in May 2021 y 001-22/036946/1 in November 2022 at CEMOSA nº 1377 (Málaga) . The results obtained were consistent for the product across all factories.

6. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.
The present declaration of performance is issued in accordance with Regulation (EU) nº2024/3110, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf
Place and date of issue: Málaga, 08/01/25



Technical director: Jose A. Ferre Martínez



1377

GRUPO PUMA ESPAÑA SL
Avda. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba)
19

PEGOLAND GEL S1 GRIS
Nº: 100595
EN 12004:2007+A1:2012

Improved deformable cementitious adhesive with reduced slip and extended open time, for floors, walls and façades, suitable for interior and exterior applications.

Reaction to fire:	Type E
Adhesion: - Initial tensile adhesion strength:	$\geq 1\text{N/mm}^2$
Durability: - Tensile adhesion after water immersion: - Tensile adhesion after heat aging: - Tensile adhesion after freeze/thaw cycles:	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$
Hazardous substances:	See safety datasheet