

DECLARATION OF PERFORMANCE

No.: 860041-01


1. **Product:**
MORCEMCAL ESTRUCTURAL
2. **Manufacturer:**
GRUPO PUMA ESPAÑA, S.L., located at:
Avda. AGRUPACIÓN CÓRDOBA, No. 17,
14014 CÓRDOBA
www.grupopuma.com
3. **Intended use:**
Rendering and plastering mortar GP CSIV W2, based on natural hydraulic lime, for external and internal rendering and plastering.
4. **Assessment system:**
4
5. **Declared performance:**

Essential characteristics	Performance	Harmonised technical specifications
Adhesion	$\geq 0,3 \text{ N/mm}^2$ Fracture pattern A/B	EN 998-1:2018
Reaction to fire	A1	
Water absorption	W2	
Water vapour diffusion coefficient	$\mu \leq 15$	
Thermal conductivity ($\lambda_{10, \text{dry}}$)	1,11	
Durability	Assessment based on provisions valid at the intended place of use of the mortar	
Dangerous substances	See Safety Data Sheet	

The performance of the product identified in point 1 is in conformity with the performance declared in point 5.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2, in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer:
Place and date of issue: Córdoba, 20/02/2026

Technical Director: Jose A. Ferre Martínez





GRUPO PUMA ESPAÑA S.L
Avda. AGRUPACIÓN CÓRDOBA, No. 17,
14014 CÓRDOBA

26

MORCEMCAL ESTRUCTURAL

No.: 860041-01

EN 998-1

Rendering and plastering mortar GP CSIV W2, based on natural hydraulic lime,
for external and internal rendering and plastering.

Reaction to fire	Class A1
Water absorption	W2
Water vapour diffusion coefficient	$\mu \leq 15$
Adhesion	$\geq 0,3 \text{ N/mm}^2$ Fracture pattern A/B