

DECLARATION OF PERFORMANCES

Nº: 860013

1. Product:
MORCEMCAL ACABADO

2. Manufacturer:
GRUPO PUMA ESPAÑA S.L located in: AVDA.
AGRUPACIÓN CÓRDOBA, Num. 17 14014
CÓRDOBA
www.grupopuma.com

3. Intended use:

Coloured render and plaster mortar CR CSI W2, based on natural hydraulic lime, for interior and exterior rendering, for finishing and final coating up to 0.8 cm thick, waterproof against rainwater.

4. Evaluation system:
4


5. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Type A1	EN 998-1:2018
Water absorption	W2	
Diffusion coefficient of water vapour	$\mu \leq 6$	
Thermal conductivity ($\lambda_{10,Dry}$)	NPD	
Adhesion	$\geq 0,1 \text{ N/mm}^2$ Shape breakage A/B	
Durability	NPD	
Hazardous substances	See safety datasheet	

The performance of the product identified in point 1 is in conformity with the declared performance set out in point 5.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 2, in accordance with Regulation (EU) No. 305/2011.

Signed by and on manufacturer behalf:
Place and Date of issue: Córdoba, 11/12/2025



Technical Director: Jose A. Ferre Martínez



GRUPO PUMA ESPAÑA S.L
AVDA. AGRUPACIÓN CÓRDOBA, Num. 17
14014 CÓRDOBA

25

MORCEMCAL ACABADO

Nº: 860013

EN 998-1

Coloured render and plaster mortar CR CSI W2, based on natural hydraulic lime, for interior and exterior rendering, for finishing and final coating up to 0.8 cm thick, waterproof against rainwater.

Reaction to fire	Type A1
Water absorption	W2
Diffusion coefficient of water vapour	$\mu \leq 6$
Adhesion	$\geq 0,1 \text{ N/mm}^2$ Shape breakage A/B
Hazardous substances	See safety datasheet