

DECLARATION OF PERFORMANCES

Nº: 100592-394

1. Product:

PEGOLAND GEL S1 BLANCO

2. Manufacturer:

GRUPO PUMA ESPAÑA SL located in:
Av. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com

3. Intended use:

Improved deformable cementitious adhesive with reduced slip and extended open time, PEGOLAND GEL S1 BLANCO, for bonding wall and floor tiles, suitable for interior and exterior applications; especially for façades, large surface floors, large-format tiles, overlays, cold rooms, underfloor heating systems, swimming pools and installation over cementitious waterproofing systems.

4. Evaluation system:

3

5. Notified bodies:

Tests were conducted under type nº 01-15/000918/1 in January 2015 and 01-18/006908/1, 01-18/006895/1 in March 2018 and 01-18/031905/1 in October 2018 and 01-18/034344/1, 01-18/036350/1 y 01-18/036351/1 in November 2018 and 01-19/030767/1 in August 2019 and 01-20/009094/1 in March 2020 and 001-22/009079/1 in March 2022 at CEMOSA nº 1377 (Málaga) . The results obtained were consistent for the product across all factories.

6. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire:	Type E	EN-12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1\text{N/mm}^2$	
Durability: - Tensile adhesion after water immersion - Tensile adhesion after heat aging - Tensile adhesion after freeze/thaw cycles	$\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$ $\geq 1\text{N/mm}^2$	
Hazardous substances:	See safety datasheet	

The performances of the product identified in point 1 comply with the performance declared in point 6.

The present declaration of performance is issued in accordance with Regulation (EU) nº2024/3110, under the sole responsibility of manufacturer stated in point 2.

Signed by and on manufacturer behalf:

Place and date of issue: Málaga, 08/01/2025



Technical director: Jose A. Ferre Martínez



1377

GRUPO PUMA ESPAÑA SL
Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba)
15

**PEGOLAND GEL S1
BLANCO**

**Nº: 100592-394
EN 12004: 2007 + A1:2012**

Improved deformable cementitious adhesive with reduced slip and extended open time, for interior and exterior floor and wall tiling.

Reaction to fire: Type E

Adhesion:
- Initial tensile adhesion strength: $\geq 1\text{N/mm}^2$

Durability:
- Tensile adhesion after water immersion: $\geq 1\text{N/mm}^2$
- Tensile adhesion after heat aging: $\geq 1\text{N/mm}^2$
- Tensile adhesion after freeze/thaw cycles: $\geq 1\text{N/mm}^2$

Hazardous substances: See safety datasheet