

DECLARATION OF PERFORMANCE


Nº: 100157

1. **Product:**
PEGOLAND FLEX GRIS
2. **Manufacturer:**
GRUPO PUMA ESPAÑA SL located in:
Avda. Agrupación Córdoba, 17
14014 Córdoba (Córdoba)
www.grupopuma.com
3. **Intended use:**
4. Improved deformable cementitious adhesive with reduced slip and extended open time, Pegoland Flex GRIS, for the installation of interior and exterior floorings, interior and exterior walls, façades, underfloor heating, cold storage rooms, large area floors and overlays, pool rendering, and installation on cement based waterproofing systems, adhesion of all type of ceramic pieces, porcelain stoneware, marble, granite, and natural stone.
5. **Evaluation system:**
3
6. **Notified bodies:**
7. Type tests were carried out under report number 79617, dated November 2004; 2504450, dated July 2005; 2525029, dated December 2006; 2811079, dated April 2008; 2829489, dated October 2009; and 0201/01/2011/005919, dated July 2011 at CEMOSA (No. 1377, Málaga). Further type tests were performed under report numbers 5029469 and 5026639, dated July and September 2005; 31212764, dated August 2006; 08/32308143, dated July 2008; and 08/32312894 and 08/32311901, dated February 2009 at APPLUS+ Laboratories (No. 0370, Barcelona), obtaining identical product performance results for all manufacturing plants.
8. **Declared performances:**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire:	E Class	EN 12004:2007+A1:2012
Adhesion: - Initial tensile adhesion strength	$\geq 1 \text{ N/mm}^2$	
Durability: - Tensile adhesion strength after water immersion - Tensile adhesion strength after heat ageing - Tensile adhesion strength after freeze-thaw cycles	$\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$ $\geq 1 \text{ N/mm}^2$	
Hazardous substances:	See Safety Data Sheet	

The performance of the product identified in point 1 conforms with the declared performance in point 6.
This Declaration of Performance is issued, in accordance with Regulation (EU) 2024/3110, under the sole responsibility of the manufacturer identified in point 2.

Signed by and on manufacturer's behalf:
Place and date of issue: Málaga, 08/01/2025



Technical Director: Jose A. Ferre Martínez

 0370, 1377	
GRUPO PUMA ESPAÑA SL Av. Agrupación Córdoba, 17. 14014 Córdoba (Córdoba) 04	
PEGOLAND FLEX GRIS Nº: 100157 EN 12004:2007+A1:2012 Improved deformable cementitious adhesive with reduced slip and extended open time, Pegoland Flex Gris, for the installation of interior and exterior floorings, interior and exterior walls, façades, underfloor heating, cold rooms, large area floors and overlays, pool rendering, and installation on cement based waterproofing systems.	
Reaction to fire:	E Class
Adhesion:	
- Initial tensile adhesion strength:	≥ 1 N/mm ²
Durability:	
- Tensile adhesion strength after water immersion:	≥ 1 N/mm ²
- Tensile adhesion strength after heat ageing:	≥ 1N/mm ²
- Tensile adhesion strength after freeze/thaw cycles:	≥ 1N/mm ²
Hazardous substances:	See Safety Data Sheet