



DECLARATION OF PERFORMANCE

No.: 230048

1.- Product:

MORCEMDRY FIX

2.-Intended use:

Single-component CM02 waterproofing membrane, fibre-reinforced, fast-setting and fast-drying, dust-free, with high flexibility and extended open time, for waterproofing applications.

3.-Manufacturer:

GRUPO PUMA ESPAÑA located at: Avda. Agrupación Córdoba 17 ,14014 Córdoba www.grupopuma.com

4.-System for assessment and verification of the constancy of product performance (AVCP):

3 for watertightness and 4 for other characteristics

5.-Notified body:

APPLUS n. 370

6.-Declared performances

Essential characteristics	Performances	Notes	Harmonized Technical Specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	A.6.2	UNE- EN-14891:2017
Water tightness	Without penetration	A.7	
Resistance to crack propagation	$\geq 0.75 \text{ mm}$	A.8 and declared conditions	
Durability of initial tensile adhesion strength against climatic action /heat ageing	$\geq 0,5 \text{ N/mm}^2$	A.6.5	
Durability of initial tensile adhesion against water /moisture	$\geq 0,5 \text{ N/mm}^2$	A.6.3 - A.6.4	
Durability of initial tensile adhesion against lime water contact	$\geq 0,5 \text{ N/mm}^2$	A.6.9	
Durability of initial tensile adhesion strength against frost and freeze/thaw cycles	$\geq 0,5 \text{ N/mm}^2$	A.6.6	
Hazardous substances	Section 4.2		

The performance of the product identified in point 1 is in conformity with the performance declared in point 6. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 3, in accordance with Regulation (EU) 2024/3110.

Signed by and on behalf of the manufacturer:

Place and date of issue: Córdoba, 26/02/26.

Technical Director: Jose A. Ferre Martínez



GRUPO PUMA ESPAÑA
Avda. Agrupación Córdoba, 17, 14014, Córdoba
25
No. 230048

UNE-EN-14891

MORCEMDRY FIX

Single-component waterproofing membrane, fibre-reinforced, fast-setting and quick-drying, dust-free, with high flexibility.

Initial tensile adhesion strength:	$\geq 0.5 \text{ N/mm}^2$
Water tightness:	No penetration
Crack bridging ability:	$\geq 0.75 \text{ mm}$
Durability of initial tensile adhesion strength against climatic action / heat ageing:	$\geq 0.5 \text{ N/mm}^2$
Durability of initial tensile adhesion strength against water action / moisture:	$\geq 0.5 \text{ N/mm}^2$
Durability of initial tensile adhesion strength against contact with lime water:	$\geq 0.5 \text{ N/mm}^2$
Durability of initial tensile adhesion strength against frost and freeze/thaw cycles:	$\geq 0.5 \text{ N/mm}^2$